

Work Order ID 150462

Wednesday, August 24, 2016 11:59:53 AM

150462

Page 1

Item ID: D3537-1

Accept

N900040100

Setup Start

NS1

Revision ID:

Stop

NS2

Item Name: Wearpad

Start Date: 8/12/2016 Start Qty: 30.00

30

Cust Item ID:

Required Date: 8/24/2016 Req'd Qty: 30.00

30

Customer:

Reference:

Approvals:

Process Plan:

DAS

21

Date:

AUG 30 2016

Tooling:

Date:

Run Start

NR1

QC:

Date:

SPC (Y/N):

Date:

Stop

NR2Sequence ID/
Work Center IDOperation
DescriptionSet Up/
Run Hours

Tool ID

Tool #

Plan
CodeAccept
QtyReject
QtyReject
NumberInsp.
Stamp

Draw Nbr

Revision Nbr

D3537

E

110

0.01

110

FLOW WATER JET

Waterjet

Memo

0.15

FLOW CNC Waterjet

1-Cut D3537-1 as per Dwg D3537

Dwg Rev: EProg Rev: E

2-Deburr if necessary

(34)

2c 11/2/09/01

120

0.00

120

QC2- Inspect parts off machine FAI/FAIB

QC

Memo

0.05

Quality Control

(34)

2c 11/2/09/01

DQA: _____ Date: _____

WORK ORDER NON-CONFORMANCE / UPDATE



QA Closed: _____ Date: _____

Work Order update only ☐

Work Order: _____ Part No. _____ NCR No. _____		DISPOSITION Rework ☐ Scrap ☐ Use-as-is ☐ Suspected Unapproved ☐		AGAINST DEPARTMENT/PROCESS Skid-tube ☐ Machining ☐ Thermoforming ☐ Large Fab ☐ Cross tube ☐ Small Fab ☐ Finishing ☐ Composite ☐ Water Jet ☐ Prod. Eng. Coord. ☐ Rec/Store/Packaging ☐ Supplier ☐ Engineering ☐ Quality ☐ Other ☐																																																											
Date :		Step #:		QTY Effective :				MRB (QSI042) Approval 																																																							
Description Work Order Deviation				Disposition																																																											
								Completed By																																																							
								Lead hand / Supervisor Approval Verification																																																							
								QC / QA Coordinator Approval																																																							
Root Cause		FAULT CATEGORY																																																													
Environment ☐	No Re-verification ☐	Pressure/Forced ☐	Temperature/Cure ☐	Power Loss/Surge ☐	Positioned Wrong ☐	Design ☐	Operator ☐	Bending ☐	Set-up ☐	Folio/Program ☐	Outside Dimensions ☐	Doc/Data ☐	Offset/Setup ☐	Centre Not Concentric ☐	BOM/Route ☐	Grain ☐	Over/Under tolerance ☐	Equip/Tooling ☐	Supplier ☐	Cracks ☐	Broken/Damage/Defect ☐	Weld ☐	Part Incorrect ☐	Handling/Pre ☐	Training ☐	Crimp/Kink/Ripple/Wave ☐	Inspection Incomplete/Unqualified ☐	Wrong Stock Pulled ☐	Part Lost/Missing ☐	Material ☐	Use for Testing ☐	Cuffs ☐	Contamination ☐	Out of Sequence ☐	Part Moved ☐	Internal Transport ☐	Poor Information ☐	Crushing ☐	Countersink ☐	Off-set ☐	Drawing ☐	Tribal Knowledge ☐	Rushing ☐	Heat Treat ☐	Cut Too Short ☐	Mislabeled ☐	Finish ☐	LOA ☐	Product Improvement ☐	Wave/Twist in Tube ☐	Instructions Incomplete/Unclear ☐	Fit/Function ☐	Misread ☐	Substation ☐	Process Improvement ☐	Marks/Chatter ☐	Drill Holes ☐	Misaligned/off center ☐	Turning Sequence ☐	Past Expiry Date ☐	Manufacturing Process ☐	OTHER :	
Misidentified ☐	Past Due ☐																																																														

DQA: _____ Date: _____



WORK ORDER NON-CONFORMANCE / UPDATE

QA Closed: _____ Date: _____

Work Order update only ☐

Work Order: _____ Part No. _____ NCR No. _____		DISPOSITION Rework ☐ Scrap ☐ Use-as-is ☐ Suspected Unapproved ☐		AGAINST DEPARTMENT/PROCESS Skid-tube ☐ Machining ☐ Thermoforming ☐ Large Fab ☐ Cross tube ☐ Small Fab ☐ Finishing ☐ Composite ☐ Water Jet ☐ Prod. Eng. Coord. ☐ Rec/Store/Packaging ☐ Supplier ☐ Engineering ☐ Quality ☐ Other ☐					
Date :		Step #:		QTY Effective :			MRB (QSI042) Approval		
Description Work Order Deviation				Disposition				Completed By	
								Lead hand / Supervisor Approval Verification	
								QC / QA Coordinator Approval	
Root Cause		FAULT CATEGORY							
Environment ☐	No Re-verification ☐	Pressure/Forced ☐	Temperature/Cure ☐	Power Loss/Surge ☐	Positioned Wrong ☐				
Design ☐	Operator ☐	Bending ☐	Set-up ☐	Folio/Program ☐	Outside Dimensions ☐				
Doc/Data ☐	Offset/Setup ☐	Centre Not Concentric ☐	BOM/Route ☐	Grain ☐	Over/Under tolerance ☐				
Equip/Tooling ☐	Supplier ☐	Cracks ☐	Broken/Damage/Defect ☐	Weld ☐	Part Incorrect ☐				
Handling/Pre ☐	Training ☐	Crimp/Kink/Ripple/Wave ☐	Inspection Incomplete/Unqualified ☐	Wrong Stock Pulled ☐	Part Lost/Missing ☐				
Material ☐	Use for Testing ☐	Cuffs ☐	Contamination ☐	Out of Sequence ☐	Part Moved ☐				
Internal Transport ☐	Poor Information ☐	Crushing ☐	Countersink ☐	Off-set ☐	Drawing ☐				
Tribal Knowledge ☐	Rushing ☐	Heat Treat ☐	Cut Too Short ☐	Mislabeled ☐	Finish ☐				
LOA ☐	Product Improvement ☐	Wave/Twist in Tube ☐	Instructions Incomplete/Unclear ☐	Fit/Function ☐	Misread ☐				
Substation ☐	Process Improvement ☐	Marks/Chatter ☐	Drill Holes ☐	Misaligned/off center ☐	Turning Sequence ☐				
Past Expiry Date ☐	Manufacturing Process ☐	OTHER : _____							
Misidentified ☐	Past Due ☐								

Work Order ID 150462

Wednesday, August 24, 2016 11:59:53 AM

150462

Page 3

Item ID: D3537-1 Accept ***N900040100*** Setup Start ***NS1***
Revision ID: Stop ***NS2***
Item Name: Wearpad
Start Date: 8/12/2016 Start Qty: 30.00 ***30*** Cust Item ID:
Required Date: 8/24/2016 Req'd Qty: 30.00 ***30*** Customer:
Reference:

Approvals: Process Plan: _____ Date: _____ Tooling: _____ Date: _____ Run Start ***NR1***
QC: _____ Date: _____ SPC (Y/N): _____ Date: _____ Stop ***NR2***

Sequence ID/ Work Center ID	Operation Description	Set Up/ Run Hours	Tool ID	Tool #	Plan Code	Accept Qty	Reject Qty	Reject Number	Insp. Stamp
160 *160* autoweld 1 Automated Welding 1	Weld per dwg & QSI004 4.5 Large Fab Memo ***SEE NOTE 8 FOR SURFACE BUILDUP*** 1- WELD AS PER DWG AND QSI004 4.5 FOR AUTOMATED WELDING USE 8259 HARDCOAT BATCH: <u>M135651</u>	0.00 0.50				34	02	16-9-20	
170 *170* QC Quality Control	QC10- Inspect visual per QSI004- ground welds Memo	0.00 0.05				34	16-09-21		DAS 9 9-89
180 *180* QC Quality Control	QC5- Inspect part completeness to step on W/O Memo	0.00 0.10				34	16-09-21		DAS 9 9-89

DQA: _____ Date: _____

WORK ORDER NON-CONFORMANCE / UPDATE



QA Closed: _____ Date: _____

Work Order update only ☐

Work Order: _____ Part No. _____ NCR No. _____		DISPOSITION Rework ☐ Scrap ☐ Use-as-is ☐ Suspected Unapproved ☐		AGAINST DEPARTMENT/PROCESS Skid-tube ☐ Machining ☐ Thermoforming ☐ Large Fab ☐ Cross tube ☐ Small Fab ☐ Finishing ☐ Composite ☐ Water Jet ☐ Prod. Eng. Coord. ☐ Rec/Store/Packaging ☐ Supplier ☐ Engineering ☐ Quality ☐ Other ☐					
Date :		Step #:		QTY Effective :				MRB (QSI042) Approval Completed By Lead hand / Supervisor Approval Verification QC / QA Coordinator Approval	
Description Work Order Deviation				Disposition					
Root Cause		FAULT CATEGORY							
Environment ☐	No Re-verification ☐	Pressure/Forced ☐	Temperature/Cure ☐	Power Loss/Surge ☐	Positioned Wrong ☐				
Design ☐	Operator ☐	Bending ☐	Set-up ☐	Folio/Program ☐	Outside Dimensions ☐				
Doc/Data ☐	Offset/Setup ☐	Centre Not Concentric ☐	BOM/Route ☐	Grain ☐	Over/Under tolerance ☐				
Equip/Tooling ☐	Supplier ☐	Cracks ☐	Broken/Damage/Defect ☐	Weld ☐	Part Incorrect ☐				
Handling/Pre ☐	Training ☐	Crimp/Kink/Ripple/Wave ☐	Inspection Incomplete/Unqualified ☐	Wrong Stock Pulled ☐	Part Lost/Missing ☐				
Material ☐	Use for Testing ☐	Cuffs ☐	Contamination ☐	Out of Sequence ☐	Part Moved ☐				
Internal Transport ☐	Poor Information ☐	Crushing ☐	Countersink ☐	Off-set ☐	Drawing ☐				
Tribal Knowledge ☐	Rushing ☐	Heat Treat ☐	Cut Too Short ☐	Mislabeled ☐	Finish ☐				
LOA ☐	Product Improvement ☐	Wave/Twist in Tube ☐	Instructions Incomplete/Unclear ☐	Fit/Function ☐	Misread ☐				
Substation ☐	Process Improvement ☐	Marks/Chatter ☐	Drill Holes ☐	Misaligned/off center ☐	Turning Sequence ☐				
Past Expiry Date ☐	Manufacturing Process ☐	OTHER : _____							
Misidentified ☐	Past Due ☐								

Work Order ID 150462

Wednesday, August 24, 2016 11:59:53 AM

150462

Page 4

Item ID: D3537-1

Accept

N900040100

Setup Start

NS1

Revision ID:

Item Name: Wearpad

Stop

NS2

Start Date: 8/12/2016 Start Qty: 30.00

30

Cust Item ID:

Required Date: 8/24/2016 Req'd Qty: 30.00

30

Customer:

Reference:

Approvals:

Process Plan: _____

Date: _____

Tooling: _____

Date: _____

Run Start

NR1

QC: _____

Date: _____

SPC (Y/N): _____

Date: _____

Stop

NR2Sequence ID/
Work Center IDOperation
DescriptionSet Up/
Run Hours

Tool ID

Tool #

Plan
CodeAccept
QtyReject
QtyReject
NumberInsp.
Stamp

210

Identify as per dwg & Stock Location: FP-001 0.00***210***

Packaging

Memo

0.05

Packaging

LOCATION : FP001

x34 d All 16/09/21

220

QC21- Final Inspection - Work Order Release 0.00

220

QC

Memo

0.50

Quality Control

DAS
21
9-89

SEP 2 1 2016

DAS
21
9-89

SEP 2 1 2016

DQA: _____ Date: _____

WORK ORDER NON-CONFORMANCE / UPDATE



QA Closed: _____ Date: _____

Work Order update only ☐

Work Order: _____ Part No. _____ NCR No. _____		DISPOSITION Rework ☐ Scrap ☐ Use-as-is ☐ Suspected Unapproved ☐		AGAINST DEPARTMENT/PROCESS Skid-tube ☐ Machining ☐ Thermoforming ☐ Large Fab ☐ Cross tube ☐ Small Fab ☐ Finishing ☐ Composite ☐ Water Jet ☐ Prod. Eng. Coord. ☐ Rec/Store/Packaging ☐ Supplier ☐ Engineering ☐ Quality ☐ Other ☐					
Date :		Step #:		QTY Effective :				MRB (QSI042) Approval	
Description Work Order Deviation				Disposition				Completed By	
								Lead hand / Supervisor Approval Verification	
								QC / QA Coordinator Approval	
Root Cause		FAULT CATEGORY							
Environment ☐	No Re-verification ☐	Pressure/Forced ☐	Temperature/Cure ☐	Power Loss/Surge ☐	Positioned Wrong ☐				
Design ☐	Operator ☐	Bending ☐	Set-up ☐	Folio/Program ☐	Outside Dimensions ☐				
Doc/Data ☐	Offset/Setup ☐	Centre Not Concentric ☐	BOM/Route ☐	Grain ☐	Over/Under tolerance ☐				
Equip/Tooling ☐	Supplier ☐	Cracks ☐	Broken/Damage/Defect ☐	Weld ☐	Part Incorrect ☐				
Handling/Pre ☐	Training ☐	Crimp/Kink/Ripple/Wave ☐	Inspection Incomplete/Unqualified ☐	Wrong Stock Pulled ☐	Part Lost/Missing ☐				
Material ☐	Use for Testing ☐	Cuffs ☐	Contamination ☐	Out of Sequence ☐	Part Moved ☐				
Internal Transport ☐	Poor Information ☐	Crushing ☐	Countersink ☐	Off-set ☐	Drawing ☐				
Tribal Knowledge ☐	Rushing ☐	Heat Treat ☐	Cut Too Short ☐	Mislabeled ☐	Finish ☐				
LOA ☐	Product Improvement ☐	Wave/Twist in Tube ☐	Instructions Incomplete/Unclear ☐	Fit/Function ☐	Misread ☐				
Substation ☐	Process Improvement ☐	Marks/Chatter ☐	Drill Holes ☐	Misaligned/off center ☐	Turning Sequence ☐				
Past Expiry Date ☐	Manufacturing Process ☐	OTHER : _____							
Misidentified ☐	Past Due ☐								

Picklist Print

Wednesday, August 24, 2016 11:59:53 AM

Page 1

Work Order ID: 150462

150462

Parent Item: D3537-1

D3537-1

Parent Item Name: Wearpad

Start Date: 8/12/2016

Required Date: 8/24/2016

Start Qty: 30.00

Required Qty: 30.00

Comments: IPP Rev:A New Issue 07-02-14 JLM
15.10.16 added automated welding DD verf:JLM

IPP REV:B

Component Item ID/ Item Name	Replacement Item ID	Mfg/ Purch	Bin Item	Primary Location	Last Location	Route Seq ID	Unit of Measure	Qty on Hand	Qty per Kit	Total Qty	Qty Issued	Date Issued	Status
M304S16GA		Purchased		No		100	sf	126.2698	0.106	3.347368			

M304S16GA

304/316 Sheet .063

08/16/09/01

Location

Loc Qty

Loc Code

MAT010

109.77

m134677

4.27

m135061

2.2

m135377

103.3

TPI

16.499794

m134604

16.499794

4

DQA: _____ Date: _____


WORK ORDER NON-CONFORMANCE / UPDATE



QA Closed: _____ Date: _____

Work Order update only ☐


Work Order: _____ Part No. _____ NCR No. _____		DISPOSITION Rework ☐ Scrap ☐ Use-as-is ☐ Suspected Unapproved ☐		AGAINST DEPARTMENT/PROCESS Skid-tube ☐ Machining ☐ Thermoforming ☐ Large Fab ☐ Cross tube ☐ Small Fab ☐ Finishing ☐ Composite ☐ Water Jet ☐ Prod. Eng. Coord. ☐ Rec/Store/Packaging ☐ Supplier ☐ Engineering ☐ Quality ☐ Other ☐																																																											
Date :		Step #:		QTY Effective :				MRB (QSI042) Approval																																																							
Description Work Order Deviation				Disposition				Completed By Lead hand / Supervisor Approval Verification QC / QA Coordinator Approval																																																							
Root Cause		FAULT CATEGORY																																																													
Environment ☐	No Re-verification ☐	Pressure/Forced ☐	Temperature/Cure ☐	Power Loss/Surge ☐	Positioned Wrong ☐	Design ☐	Operator ☐	Bending ☐	Set-up ☐	Folio/Program ☐	Outside Dimensions ☐	Doc/Data ☐	Offset/Setup ☐	Centre Not Concentric ☐	BOM/Route ☐	Grain ☐	Over/Under tolerance ☐	Equip/Tooling ☐	Supplier ☐	Cracks ☐	Broken/Damage/Defect ☐	Weld ☐	Part Incorrect ☐	Handling/Pre ☐	Training ☐	Crimp/Kink/Ripple/Wave ☐	Inspection Incomplete/Unqualified ☐	Wrong Stock Pulled ☐	Part Lost/Missing ☐	Material ☐	Use for Testing ☐	Cuffs ☐	Contamination ☐	Out of Sequence ☐	Part Moved ☐	Internal Transport ☐	Poor Information ☐	Crushing ☐	Countersink ☐	Off-set ☐	Drawing ☐	Tribal Knowledge ☐	Rushing ☐	Heat Treat ☐	Cut Too Short ☐	Mislabeled ☐	Finish ☐	LOA ☐	Product Improvement ☐	Wave/Twist in Tube ☐	Instructions Incomplete/Unclear ☐	Fit/Function ☐	Misread ☐	Substation ☐	Process Improvement ☐	Marks/Chatter ☐	Drill Holes ☐	Misaligned/off center ☐	Turning Sequence ☐	Past Expiry Date ☐	Manufacturing Process ☐	OTHER :	
Misidentified ☐	Past Due ☐																																																														



D3537-1F WEARPAD
(FLAT PATTERN)


NOTES:

- 1) MATERIAL: AISI 304/316 STAINLESS STEEL 16 GAUGE 0.063 THICK
PER MIL-S-5059 OR AMS 5513 OR 5524 OR ASTM A240 OR ASME SA240
REF DART SPEC. M304S16GA
- 2) FINISH: NONE
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY PER QSI 044 6.1
- 7) WEIGHT: 0.42 lbs
- 8) BUILDUP HARD SURFACING 0.17 - 0.20 THICK USING 8259 ROD PER QSI 004 SECTION 4.5 (AUTOMATED WELDING) OR
BUILDUP HARD SURFACING 0.19 - 0.25 THICK USING 2059B ROD PER QSI 004 SECTION 4.1 (MANUAL WELDING)




D3537-1 WEARPAD
MAKE FROM D3537-1F

SHOP COPY
RETURN TO
ENGINEERING
UNCONTROLLED COPY
SUBJECT TO AMENDMENT
WITHOUT NOTICE
WORK ORDER
NO. 150462 MJS
16-08-30




RELEASED
2015-12-07
EUN 15-651


E	-5 DELETED PART IS OBSOLETE. RE-FORMAT. NOTE 8 RE-WRITTEN FOR ROBOTIC WELDING. SHEETS 1 & 2 SLOT DIMENSION UPDATED.	AJS	15.09.28
D	RE-FORMAT DRAWING, ADD -9/-11 WEARPADS	DB	14.10.16
C	WIDEN TAB TO 0.380, WEL PATTERN	CB	07.04.13
B	ADD AMS5510 AND AMS 5524	CB	07.03.20
A	NEW ISSUE	CB	06.11.06
REV.	DESCRIPTION	BY	DATE
DESIGN	CB	DART AEROSPACE USA, INC. EUGENE, OR	
DRAWN	AJS		
CHECKED	AP	DRAWING NO.	REV. E
MFG. APPR.	JLM	D3537	SHEET 1 OF 5
APPROVED	WM	TITLE	SCALE
DE APPR.	DS	WEARPAD	NTS
DATE	15.09.28	COPYRIGHT © 2006 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL, AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	



SECTION A-A




**D3537-3 WEARPAD
(BENDING DETAIL)
(MAKE FROM D3537-3F)**



0.3
2 PL

**D3537-3 WEARPAD
(WELDMENT)**



**D3537-3F WEARPAD
(FLAT PATTERN)**



NOTES:

- 1) MATERIAL: AISI 304/316 STAINLESS STEEL 16 GAUGE 0.063 THICK
PER MIL-S-5059 OR AMS 5513 OR 5524 OR ASTM A240 OR ASME SA240
REF DART SPEC. M304S16GA
- 2) FINISH: NONE
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY PER QSI 044 6.1
- 7) WEIGHT: 0.50 lbs
- 8) BUILDUP HARD SURFACING 0.17 - 0.20 THICK USING 8259 ROD PER QSI 004 SECTION 4.5 (AUTOMATED WELDING) OR
BUILDUP HARD SURFACING 0.19 - 0.25 THICK USING 2059B ROD PER QSI 004 SECTION 4.1 (MANUAL WELDING)

RELEASED
2015-12-07

APPROVED

DESIGN	CB	DART AEROSPACE USA, INC.	
DRAWN	AJS	EUGENE, OR	
CHECKED	AP	DRAWING NO.	REV. E
MFG. APPR.	JLM	D3537	SHEET 2 OF 5
APPROVED	WM	TITLE	SCALE
DE APPR.	DS	WEARPAD	NTS
DATE	15.09.28	COPYRIGHT © 2006 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRELIMINARY AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	



D3537-7 WEARPAD
(MAKE FROM D3537-3F)



NOTES:

- 1) MATERIAL: MAKE FROM -3F
- 2) FINISH: NONE
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY PER QSI 044 6.1
- 7) WEIGHT: 0.50 lbs
- 8) BUILDUP HARD SURFACING 0.17 - 0.20 THICK USING 8259 ROD PER QSI 004 SECTION 4.5 (AUTOMATED WELDING) OR BUILDUP HARD SURFACING 0.19 - 0.25 THICK USING 2059B ROD PER QSI 004 SECTION 4.1 (MANUAL WELDING)

RELEASED
2015-12-07

APPROVED

DESIGN	CB	DART AEROSPACE USA, INC.	
DRAWN	AJS	EUGENE, OR	
CHECKED	AP	DRAWING NO.	REV. E
MFG. APPR.	JLM	D3537	SHEET 3 OF 5
APPROVED	WM	TITLE	SCALE
DE APPR.	DS	WEARPAD	NTS
DATE	15.09.28	COPYRIGHT © 2008 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	



D3537-9 WEARPAD
(MAKE FROM D3537-1F)


NOTES:

- 1) MATERIAL : MAKE FROM -1F
- 2) FINISH: NONE
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY PER QSI 044 6.1
- 7) WEIGHT: 0.19 lbs
- 8) APPLY HARD SURFACING WELD BEAD 0.06 - 0.13 THICK USING 8259 ROD PER QSI 004 SECTION 4.5 (AUTOMATED WELDING) OR
APPLY HARD SURFACING WELD BEAD 0.06 - 0.13 THICK USING 2059B ROD PER QSI 004 SECTION 4.1 (MANUAL WELDING)
- 9) COAT ENTIRE TOP (CONCAVE) SURFACE WITH TEXTURED COATING, 0.02-0.04 THICK, PER DART QSI 005 4.9


RELEASED
2015-12-07

APPROVED


DESIGN	CB	DART AEROSPACE USA, INC.	
DRAWN	AJS	EUGENE, OR	
CHECKED	AP	DRAWING NO.	REV. E
MFG. APPR.	JLM	D3537	SHEET 4 OF 5
APPROVED	WM	TITLE	SCALE
DE APPR.	DS	WEARPAD	NTS
DATE	15.09.28	COPYRIGHT © 2008 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	



SECTION B-B



D3537-11 WEARPAD
(BENDING DETAIL)
(MAKE FROM D3537-3F)



D3537-11 WEARPAD
(WELDMENT)

NOTES:

- 1) MATERIAL: MAKE FROM -3F
- 2) FINISH: NONE
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY PER QSI 044 6.1
- 7) WEIGHT: 0.25 lbs
- 8) APPLY HARD SURFACING WELD BEAD 0.06 - 0.13 THICK USING 8259 ROD PER QSI 004 SECTION 4.5 (AUTOMATED WELDING) OR
APPLY HARD SURFACING WELD BEAD 0.06 - 0.13 THICK USING 2059B ROD PER QSI 004 SECTION 4.1 (MANUAL WELDING)
- 9) COAT ENTIRE TOP (CONCAVE) SURFACE WITH TEXTURED COATING, 0.02-0.04 THICK, PER DART QSI 005 4.9

RELEASED
2015-12-07

APPROVED

DESIGN	CB	DART AEROSPACE USA, INC.	
DRAWN	AJS	EUGENE, OR	
CHECKED	AP	DRAWING NO.	REV. E
MFG. APPR.	JLM	D3537	SHEET 5 OF 5
APPROVED	WM	TITLE	SCALE
DE APPR.	DS	WEARPAD	NTS
DATE	15.09.28	COPYRIGHT © 2006 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	